



# technical specification pb-8002 protocole®

## PHYSICAL DIMENSIONS

### 10 panels PB-8002

**Standard Dimensions Outside: 171,4 cm x 194,5 cm x 173,5 cm**

**Acoustic Environment: Surpasses ISO-4043 International Standard (last version)**

STANDARD	DIMENSION	WEIGHT
Standard panel (3)	85,7 cm x 194,5 cm	10,00 kg
Window panel (4)	85,7 cm x 194,5 cm	14,10 kg
Door panel (1)	85,7 cm x 194,5 cm	17,00 kg
Roof panel (2)	85,7 cm x 173,5 cm	7,70 kg
<b>Total booth Weight</b>		<b>118,80 kg</b>

• **Standard outside color:** Dark grey or light grey (ABS plastic finish)

• **Standard inside color:** Light grey or dark blue

**Assembly:** No tools required

**Approx. Assembly time:** 10 Minutes (2 persons)

**STORAGE & SHIPPING:** **Included (1) ATA-300 shipping cases** on wheels (52,5 Kg)  
CASE OUTSIDE - DIM. : 207,1 x 45,72 x 109,22 cm

**AIR VENTILATION:** Included (2) H.D. 55 CFM silent whisper 110 or 220 volts fan assembly units CSA approved with (2) electric outlets for accessories.

**OPTIONS:** Easy to install working table, double Plexiglas® window, air conditioning  
Sound proof flooring, interior division partition systems.

**CONSTRUCTION:** Each panel is built with ABS plastic exterior with special isolated soundproof fibreglass panel. Material is fire retardant UL-723. Inside covering is made with decorative textile 100 % polyester. Cotton of 9 mm. Woven density and weight of 60 gr. Per meter. Framing is PVC extrusion with unique connecting concept with industrial Velcro for easy assembly without tools.



